## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

## 1-5. (Cancelled)

6. (Original) An image forming system comprising a scanner for scanning an image of a document to output an image signal and a printer for copying the image onto an image receiving medium in response to the image signal, wherein:

the system comprises scanning magnification setting means for setting a scanning magnification when the scanner scans the document;

the scanner includes a delay memory for temporarily storing the image signal and then outputting the image signal;

the printer includes feeding means for feeding the image receiving medium; and the system is configured so as to change relative timing between timing at which the image signal is output from the delay memory and timing at which the image receiving medium is fed by the feeding means in accordance with the scanning magnification set by the scanning magnification setting means.

- 7. (Original) The image forming system according to claim 6, wherein the relative timing is changed such that a size of a margin between a leading edge of the image receiving medium and that of the image copied onto the image receiving medium is fixed irrespective of the scanning magnification.
  - 8. (Original) A color image forming apparatus comprising: optical means for reading a color image of a document;

an image sensor for scanning the color image read by the optical means in a main scanning direction and a sub-scanning direction perpendicular to the main scanning direction

and outputting image signals of different colors from the color image, the image sensor including a plurality of line sensors arranged at given intervals in the sub-scanning direction;

timing correction means for correcting a difference in timing between the image signals of different colors which is caused by the given intervals in the sub-scanning direction of the plurality of line sensors;

copying means for copying the color image of the document onto an image receiving medium in response to the image signals of different colors whose timing difference is corrected by the timing correction means;

reading magnification setting means for setting a reading magnification of the document; and

timing control means for changing at least one of operation timing of the image sensor and that of the copying means based on a specific reading magnification set by the reading magnification setting means.

- 9. (Original) The color image forming apparatus according to claim 8, wherein the image sensor includes three line sensors having a number of photoelectric converting elements arranged in the main scanning direction, and the three line sensors are arranged in parallel at regular intervals in the sub-scanning direction and including a first primary-color line sensor, a second primary-color line sensor, and a third primary-color line sensor.
- 10. (Original) The color image forming apparatus according to claim 9, wherein the timing correcting means includes a first delay circuit for delaying a first-color image signal sensed by the first primary-color line sensor by a time period which is twice as long as each of the regular intervals and a second delay circuit for delaying a second-color image signal sensed by the second primary-color line sensor by a time period corresponding to each of the regular intervals.

11. (Original) The color image forming apparatus according to claim 10, wherein the timing correcting means further includes a delay circuit for simultaneously storing the first-color image signal delayed by the first delay circuit, the second-color image signal delayed by the second delay circuit, and a third-color image signal sensed by the hird primary-color line sensor, and simultaneously outputting the first-color image signal, the second-color image signal, and the third-color image signal after a lapse of a predetermined period of time.

## 12-13. (Cancelled)

14. (Original) An image forming method using a system including a scanner for scanning an image of a document to output an image signal, a printer for copying the image onto an image receiving medium in response to the image signal, and scanning magnification setting means for setting a scanning magnification when the scanner scans the document, the scanner including a delay memory for temporarily storing the image signal and then outputting the image signal, and the printer including feeding means for feeding the image receiving medium, the method comprising:

checking whether the scanning magnification is changed; and

varying relative timing between timing at which the image signal is output from the delay memory and timing at which the image receiving medium is fed by the feeding means in accordance with the scanning magnification changed by the scanning magnification setting means.

15. (Currently Amended) The image forming method according to claim 14, wherein the relative timing is changed such that a size of a margin between a leading edge of the image receiving medium and that a leading edge of the image copied onto the image receiving medium is fixed irrespective of a change in the scanning magnification.